

ICE28N60VFB N-Channel Enhancement Mode MOSFET

RoHS compliant
2011/65/EU




HALOGEN
FREE

Product Summary			
I_D	$T_A=25^\circ\text{C}$	28A	Max
BV_{DSS}	$I_D=250\mu\text{A}$	600V	Min
$r_{DS(on)}$	$V_{GS}=10\text{V}$	0.107 Ω	Typ
Q_g	$V_{DS}=480\text{V}$	80nC	Typ

Features

- Low $r_{DS(on)}$
- Ultra Low Gate Charge
- High dv/dt capability
- High Unclamped Inductive Switching (UIS) capability
- High peak current capability
- Optimized design for hard switching SMPS topologies



T0263 (D²PAK)

Standard Metal Heatsink

1=Gate, 2=Drain, 3=Source.

ICEMOS AND ITS SISTER COMPANY 3D SEMI OWN THE FUNDAMENTAL PATENTS FOR SUPERJUNCTION MOSFETS. THE MAJORITY OF THESE PATENTS HAVE 17 to 20 YEARS OF REMAINING LIFE. THIS PORTFOLIO HAS GRANTED PATENTS ISSUED IN USA, CHINA, KOREA, JAPAN, TAIWAN & EUROPE.

Maximum ratings at $T_j=25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	$T_c=25^\circ\text{C}$	28	A
		$T_c=100^\circ\text{C}$	18	
Pulsed drain current ^a	$I_{D, pulse}$	$T_c=25^\circ\text{C}$	75	A
Avalanche energy, single pulse	E_{AS}	$I_D=7\text{A}$	691	mJ
Avalanche current, repetitive	I_{AR}	limited by T_{jmax}	7	A
MOSFET dv/dt ruggedness	dv/dt	$V_{DS}=480\text{V}$, $I_D=28\text{A}$, $T_j=125^\circ\text{C}$	70	V/ns
Gate source voltage	V_{GS}	Static	± 20	V
		AC ($f>1\text{Hz}$)	± 30	
Power dissipation	P_{tot}	$T_c=25^\circ\text{C}$	250	W
Operating and storage temperature	T_j, T_{stg}		-55 to +150	$^\circ\text{C}$

^a Pulse width t_p limited by T_{jmax}

Parameter	Symbol	Conditions	Values			Unit
			Min	Typ	Max	

Thermal characteristics

Thermal resistance, junction-case ^a	R_{thJC}		-	-	0.5	°C/W
Thermal resistance, junction-ambient ^a	R_{thJA}	leaded	-	-	62	
Soldering temperature, wave soldering only allowed at leads	T_{sold}	1.6mm (0.063in.) from case for 10 s	-	-	260	°C

Electrical characteristics at $T_j=25^{\circ}\text{C}$, unless otherwise specified

Static characteristics

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}, I_D=250\mu\text{A}$	600	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	2	-	4	
Zero gate voltage drain current	I_{DSS}	$V_{DS}=480\text{V}, V_{GS}=0\text{V}, T_j=25^{\circ}\text{C}$	-	-	1	uA
		$V_{DS}=480\text{V}, V_{GS}=0\text{V}, T_j=125^{\circ}\text{C}$	-	-	2	mA
Gate source leakage current	I_{GSS}	$V_{GS}=\pm 20\text{ V}, V_{DS}=0\text{V}$	-	-	100	nA
Drain-source on-state resistance	$r_{DS(on)}$	$V_{GS}=10\text{V}, I_D=14\text{A}, T_j=25^{\circ}\text{C}$	-	0.107	0.123	Ω
		$V_{GS}=10\text{V}, I_D=14\text{A}, T_j=150^{\circ}\text{C}$	-	0.28	-	Ω
Gate resistance	R_G	$f=1\text{ MHz}, \text{open drain}$	-	0.77	-	Ω

Dynamic characteristics

Input capacitance	C_{iss}	$V_{GS}=0\text{ V}, V_{DS}=100\text{ V}, f=1\text{ MHz}$	-	2714	-	pF
Output capacitance	C_{oss}		-	123	-	
Reverse transfer capacitance	C_{rss}		-	6	-	
Transconductance	g_{fs}	$V_{DS}=30\text{V}, I_D=14\text{A}$	-	9.7	-	S
Turn-on delay time	$t_{d(on)}$	$V_{DS}=480\text{V}, V_{GS}=10\text{V}, I_D=14\text{A}, R_G=9.1\Omega \text{ (External)}$	-	24	48	ns
Rise time	t_r		-	40	80	
Turn-off delay time	$t_{d(off)}$		-	82	123	
Fall time	t_f		-	38	78	

Parameter	Symbol	Conditions	Values			Unit
			Min	Typ	Max	


Gate charge characteristics

Gate to source charge	Q_{gs}	$V_{DS}=480\text{ V}, I_D=14\text{ A},$ $V_{GS}=10\text{ V}$	-	17	-	nC
Gate to drain charge	Q_{gd}		-	33	-	
Gate charge total	Q_g		-	80	120	
Gate plateau voltage	$V_{plateau}$		-	6	-	V


Reverse Diode

Continuous forward current	I_S	$V_{GS}=0\text{ V}$	-	-	28	A
Diode forward voltage	V_{SD}	$V_{GS}=0\text{ V}, I_S=11\text{ A}$	-	0.9	1.2	V
Reverse recovery time	t_{rr}	$V_{RR}=25\text{ V}, I_S=I_F=14\text{ A},$ $d_{iF}/d_t=100\text{ A}/\mu\text{S}$	-	142	284	ns
Reverse recovery charge	Q_{rr}		-	0.97	1.94	μC
Peak reverse recovery current	I_{rm}		-	13.2	-	A


Output Characteristics




Transfer Characteristics




Drain-Source On-resistance vs. Junction Temperature




Drain-Source Breakdown Voltage vs. Junction Temperature




Gate Charge




Capacitance




Source-Drain Diode Forward Voltage




Maximum Rated Forward Biased Safe Operating Area



Transient Thermal Response, Junction-to-Ambient



Package Outline: TO-263 D²PAK



COMMON DIMENSIONS

SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX
A	4.40	4.57	4.70	0.173	0.180	0.185
A1	0	0.10	0.25	0	0.004	0.010
A2	2.59	2.69	2.79	0.102	0.106	0.110
b	0.77	–	0.90	0.030	–	0.035
b1	1.23	–	1.36	0.048	–	0.054
c	0.34	–	0.47	0.013	–	0.019
C1	1.22	–	1.32	0.048	–	0.052
D	8.60	8.70	8.80	0.338	0.343	0.346
E	10.06	10.16	10.26	0.396	0.4	0.404
e	2.54BSC			0.1BSC		
H	14.70	15.10	15.50	0.579	0.594	0.610
L	2.00	2.30	2.60	0.079	0.090	0.102
L3	1.17	1.27	1.40	0.046	0.050	0.055
L1	–	–	1.70	–	–	0.067
L4	0.25BSC			0.01BSC		
L2	2.50REF			0.098REF		
θ	0°	–	8°	0°	–	8°
θ ₁	5°	7°	9°	5°	7°	9°
θ ₂	1°	3°	5°	1°	3°	5°
DEP	0.05	0.10	0.20	0.002	0.004	0.008
φ _{p1}	1.40	1.50	1.60	0.055	0.059	0.063

ICEMOS SUPERJUNCTION PATENT PORTFOLIO

ICEMOS GRANTED PATENTS

US7,429,772

US7,439,178

US7,446,018

US7,579,607

US7,723,172

US7,795,045

US7,846,821

US7,944,018

US8,012,806

US8,030,133

3D SEMI PATENTS LICENSED TO ICEMOS

US7,041,560B2

US7,023,069B2

US7,364,994

US7,227,197B2

US7,304,944B2

US7,052,982B2

US7,339,252

US7,410,891

US7,439,583

US7,227,197B2

US6,635,906

US6,936,867

US7,015,104

US9,109,110

US7,271,067

US7,354,818

US7,052,982,

US7,199,006B2

Note: additional patents in China, Korea, Japan, Taiwan, Europe have also been granted to IceMOS and 3D Semi for Superjunction MOSFETs with 70 additional Patent applications in process in the USA and the above listed countries.

Marking Information

YY = Last two digits of the year

WW = Work week calendar on Icemos subcon assembly & test house

Z = Assembly location ID

XXXXXX = Lot ID

ICE28N60VF = ICE is Icemos logo and 28N60VF is a designated device part number

