

ICE13N60 N-Channel Enhancement Mode MOSFET


Features

- Low $r_{DS(on)}$
- Ultra Low Gate Charge
- High dv/dt capability
- High Unclamped Inductive Switching (UIS) capability
- High peak current capability
- Increased transconductance performance
- Optimized design for high performance power systems



Lead Free

Product Summary			
I_D	$T_A=25^\circ\text{C}$	13A	Max
$V_{(BR)DSS}$	$I_D=250\mu\text{A}$	600V	Min
$r_{DS(on)}$	$V_{GS}=10\text{V}$	0.23	Typ
Q_g	$V_{DS}=480\text{V}$	48nC	Typ



T0220

Standard Metal Heatsink

1=Gate, 2=Drain, 3=Source.

ICEMOS OWNS THE FUNDAMENTAL PATENTS FOR SUPERJUNCTION MOSFETS. THE MAJORITY OF THESE PATENTS HAVE 17 to 20 YEARS OF REMAINING LIFE. THIS PORTFOLIO HAS GRANTED PATENTS ISSUED IN USA, CHINA, KOREA, JAPAN, TAIWAN & EUROPE.

Maximum ratings^b, at $T_j=25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current ^a	I_D	$T_c=25^\circ\text{C}$	13	A
		$T_c=100^\circ\text{C}$	8	
Pulsed drain current	$I_{D, \text{pulse}}$	$T_c=25^\circ\text{C}$	39	A
Avalanche energy, single pulse	E_{AS}	$I_D=6.5\text{A}$	211	mJ
Avalanche current, repetitive	I_{AR}	limited by $T_{j\text{max}}$	6.5	A
MOSFET dv/dt ruggedness	dv/dt	$V_{DS}=480\text{V}$, $I_D=13\text{A}$, $T_j=125^\circ\text{C}$	50	V/ns
Gate source voltage	V_{GS}	Static	± 20	V
		AC ($f>1\text{Hz}$)	± 30	
Power dissipation	P_{tot}	$T_c=25^\circ\text{C}$	128	W
Operating and storage temperature	T_j, T_{stg}		-55 to +150	$^\circ\text{C}$
Mounting torque		M 3 & 3.5 screws	60	Ncm

^a When mounted on 1inch square 2oz copper clad FR-4

^b Pulse width limited by $T_{j\text{max}}$

Parameter	Symbol	Conditions	Values			Unit
			Min	Typ	Max	

Thermal characteristics

Thermal resistance, junction-case ^a	R_{thJC}		-	-	0.97	°C/W
Thermal resistance, junction-ambient ^a	R_{thJA}	leaded	-	-	62	
Soldering temperature, wave soldering only allowed at leads	T_{sold}	1.6mm (0.063in.) from case for 10 s	-	-	260	°C

Electrical characteristics ^b, at $T_j=25^{\circ}\text{C}$, unless otherwise specified

Static characteristics

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}$, $I_D=250\mu\text{A}$	600	640	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$, $I_D=250\mu\text{A}$	2.1	3	3.9	
Zero gate voltage drain current	I_{DSS}	$V_{DS}=600\text{V}$, $V_{GS}=0\text{V}$, $T_j=25^{\circ}\text{C}$	-	0.1	1	μA
		$V_{DS}=600\text{V}$, $V_{GS}=0\text{V}$, $T_j=150^{\circ}\text{C}$	-	100	-	
Gate source leakage current	I_{GSS}	$V_{GS}=\pm 20\text{ V}$, $V_{DS}=0\text{V}$	-	-	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$V_{GS}=10\text{V}$, $I_D=6.5\text{A}$, $T_j=25^{\circ}\text{C}$	-	0.23	0.27	Ω
		$V_{GS}=10\text{V}$, $I_D=6.5\text{A}$, $T_j=150^{\circ}\text{C}$	-	0.64	-	
Gate resistance	R_G	$f=1\text{ MHz}$, open drain	-	3.5	-	Ω

Dynamic characteristics

Input capacitance	C_{iss}	$V_{GS}=0\text{ V}$, $f=1\text{ MHz}$	$V_{DS}=25\text{ V}$	-	1575	-	pF
Output capacitance	C_{oss}		$V_{DS}=100\text{ V}$	-	5.3	-	
Reverse transfer capacitance	C_{rss}		$V_{DS}=25\text{ V}$	-	62	-	
Transconductance	g_{fs}	$V_{DS}>2 \cdot I_D \cdot R_{DS}$, $I_D=6.5A$		-	9.5	-	S
Turn-on delay time	$t_{d(on)}$	$V_{DS}=380V$, $V_{GS}=10V$, $I_D=6.5A$, $R_G=4\Omega$ (External)		-	13.2	-	ns
Rise time	t_r			-	19.7	-	
Turn-off delay time	$t_{d(off)}$			-	50	-	
Fall time	t_f			-	14.4	-	

Parameter	Symbol	Conditions	Values			Unit
			Min	Typ	Max	


Gate charge characteristics

Gate to source charge	Q_{gs}	$V_{DS}=480\text{ V}, I_D=13\text{ A},$ $V_{GS}=0\text{ to }10\text{ V}$	-	12.2	-	nC
Gate to drain charge	Q_{gd}		-	14.6	-	
Gate charge total	Q_g		-	37.5	-	
Gate plateau voltage	$V_{plateau}$		-	8.1	-	V


Reverse Diode

Continuous forward current	I_S	$V_{GS}=0\text{ V}$	-	-	13	A
Diode forward voltage	V_{SD}	$V_{GS}=0\text{ V}, I_S=I_F$	-	0.9	1.2	V
Reverse recovery time	t_{rr}	$V_{RR}=480\text{ V}, I_S=I_F,$ $d_{iF}/d_t=100\text{ A}/\mu\text{S}$	-	285	-	ns
Reverse recovery charge	Q_{rr}		-	4.2	-	μC
Peak reverse recovery current	I_{rm}		-	29.5	-	A


Output Characteristics




Transfer Characteristics




Drain - Source On-State Resistance vs. Drain Current




Drain-Source On-State Resistance vs. Gate-to-Source Voltage









Drain - Source On State Resistance vs. Junction Temperature




Gate Threshold Voltage vs. Junction Temperature





Package Outline: TO-220



Package Outline: TO-220

SYMBOL	Unit :mm		
	MIN	NOM	MAX
A	4.37	4.57	4.77
A1	1.22	1.27	1.42
A2	2.49	2.69	2.89
b	0.75	0.81	0.96
b2	1.22	1.27	1.47
c	0.30	0.38	0.48
D1	8.50	8.70	8.90
D2	12.00	12.40	12.80
E	9.86	10.16	10.36
E5	6.80	8.20	8.60
e	2.54 BSC		
e1	5.08 BSC		
H1	6.10	6.30	6.50
L	13.10	13.40	13.70
L1	-	3.75	4.10
L3	15.80	16.00	16.40
ΦP	3.70	3.84	3.99
Q	2.54	2.74	2.94

Marking Information


YY = Last two digits of the year

WW = Work week

***** = Site ID

XXXXXX = Lot ID

ICE13N60 = ICE is IceMOS logo and 13N60 is a designated device part number



Disclaimer

Information contained in this data sheet shall in no event be regarded as a guarantee of conditions or characteristics. All product, data sheet are subject to change without notice to improve reliability. ICEMOS technology will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet.