



ICEK42NF60W N-Channel Enhancement Mode MOSFET

Features

- TO247-3L package
- Ultra Low $r_{DS(on)}$
- Ultra Low Gate Charge
- High dv/dt capability
- Ultra Fast Recovery Body Diode
- High Unclamped Inductive Switching (UIS) capability
- High peak current capability
- Increased transconductance performance
- Optimized design for high performance power systems

Product Summary			
I_D	$T_A=25^\circ\text{C}$	42A	Max
$V_{(BR)DSS}$	$I_D=1\text{mA}$	600V	Min
$r_{DS(on)}$	$V_{GS}=10\text{V}$	45m Ω	Typ
Q_g	$V_{DS}=400\text{V}$	95nC	Typ



TO247
1:G, 2:D,
3:S
(TO-247)



Lead Free

Maximum ratings ^a at $T_j=25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current ^b	I_D	$T_c=25^\circ\text{C}$ $T_c=100^\circ\text{C}$	42 27	A
Pulsed drain current ^b	$I_{D, pulse}$	$T_c=25^\circ\text{C}$	150	A
Avalanche energy, single pulse	E_{AS}	$L = 10.8 \text{ mH}, V_{DD} = 100 \text{ V}, I_D=10\text{A}, R_G = 50 \Omega$	540	mJ
Avalanche current, repetitive ^b	I_{AR}	limited by T_{jmax}	10	A
MOSFET dv/dt ruggedness	dv/dt	$V_{DS}=400\text{V}, I_D=42\text{A}, T_j=125^\circ\text{C}$	120	V/ns
Reverse diode dv/dt			70	
Gate source voltage	V_{GS}	Static	± 30	V
		AC ($f > 1\text{Hz}$)		
Power dissipation	P_{tot}	$T_c=25^\circ\text{C}$	250	W

^a Preliminary data sheet - Specifications subject to change.

^b limited by T_{jmax}

^c when mounted on 1-inch square 2oz copper-clad FR-4

Parameter	Symbol	Conditions	Values			Unit
			Min	Typ	Max	

Thermal characteristics

Thermal resistance, junction-case ^{a,c}	R_{thJC}		-	-	0.5	°C/W
Thermal resistance, junction-ambient ^{a,c}	R_{thJA}	leaded	-	-	30	

Electrical characteristics at $T_j=25^\circ\text{C}$, unless otherwise specified

Static characteristics

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}, I_D=1\text{ mA}$	600	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=1\text{ mA}$	3	3.8	5	
Zero gate voltage drain current	I_{DSS}	$V_{DS}=600\text{ V}, V_{GS}=0\text{ V}$	-	-	10	μA
Gate source leakage current	I_{GSS}	$V_{GS}=\pm 30\text{ V}, V_{DS}=0\text{ V}$	-	-	±100	nA
Drain-source on-state resistance	$r_{DS(on)}$	$V_{GS}=10\text{ V}, I_D=16\text{ A}$	-	45	58	mΩ
Gate resistance	R_G	$f=1\text{ MHz}$, open drain	-	6	-	Ω

Dynamic characteristics

Input capacitance	C_{iss}	$V_{GS}=0\text{ V}, V_{DS}=400\text{ V}, f=1\text{ MHz}$	-	2890	-	pF
Reverse transfer capacitance	C_{rss}		-	15	-	
Output capacitance	C_{oss}		-	63	-	
Effective output capacitance, energy related	$C_{o(er)}$	$V_{GS}=0\text{ V}, V_{DS}=0\text{ to }400\text{ V}$	-	129	-	pF
Effective output capacitance, time related	$C_{o(tr)}$	$V_{GS}=0\text{ V}, V_{DS}=0\text{ to }400\text{ V}, I_D=\text{constant}$	-	990	-	pF
Turn-on delay time	$t_{d(on)}$	$V_{DS}=400\text{ V}, V_{GS}=13\text{ V}, I_D=16\text{ A}, R_G=3\Omega$ (External)	-	95	-	ns
Rise time	t_r		-	8	-	
Turn-off delay time	$t_{d(off)}$		-	83	-	
Fall time	t_f		-	8	-	

Parameter	Symbol	Conditions	Values			Unit
			Min	Typ	Max	

Gate charge characteristics

Gate to source charge	Q_{gs}	$V_{DS}=400\text{ V}, I_D=16\text{ A},$ $V_{GS}=0\text{ to }10\text{ V}$	-	16	-	nC
Gate to drain charge	Q_{gd}		-	50	-	
Gate charge total	Q_g		-	95	-	

Reverse Diode

Continuous forward current	I_S	$V_{GS}=0\text{ V}$	-	-	42	A
Pulsed forward current	I_{SM}		-	-	150	A
Diode forward voltage	V_{SD}	$V_{GS}=0\text{ V}, I_S=I_{rm}$	-	0.95	-	V
Reverse recovery time	t_{rr}	$V_{RR}=400\text{ V}, I_S=I_{rm},$ $d_{iF}/dt=100\text{ A}/\mu\text{S}$	-	90	-	ns
Reverse recovery charge	Q_{rr}		-	0.8	-	μC
Peak reverse recovery current	I_{rm}		-	16	-	A




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: Breakdown Voltage vs. Junction Temperature




Figure 6: Threshold Voltage vs. Junction Temperature




Figure 7: Body-Diode Characteristics




Figure 8: On-Resistance vs. Gate-Source Voltage




Figure 9: Capacitance Characteristics




Figure 10: Gate-Charge Characteristics




Figure 11: Power De-rating




Figure 12: Current De-rating




Figure 13: Normalized Maximum Transient Thermal Impedance




Figure 14: Maximum Forward Biased Safe Operating Area

Marking Information


YY = Last two digits of the year

WW = Work week

***** = Site ID

XXXXXX = Lot ID

ICEK42NF60 = ICE is Icmos logo and
K42NF60 is a designated device part
number



Disclaimer

Information contained in this data sheet shall in no event be regarded as a guarantee of conditions or characteristics. All product, data sheet are subject to change without notice to improve reliability. ICEMOS technology will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet.