



ICE80M120W Silicon Carbide Power MOSFET

Features

- 1200V 80mohm SiC MOSFET
- High blocking voltage with low $R_{DS(ON)}$
- Fast switching speed with low capacitances
- Fast intrinsic diode with low reverse recovery (Q_{RR})
- Optimized design for high performance power systems

Product Summary			
I_D	$T_A=25^\circ\text{C}$	35.1A	Max
$V_{(BR)DSS}$	$T_C=25^\circ\text{C}$	1200V	Min
$r_{DS(on)}$	$V_{GS}=18\text{V}$	80m Ω	Typ
Q_g	$V_{DS}=800\text{V}$	68.6nC	Typ



TO247
1:G, 2:D,
3:S
(TO-247)



Lead Free

Maximum ratings^a, at $T_j=25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	$T_c=25^\circ\text{C}$	35.1	A
		$T_c=100^\circ\text{C}$	24.8	
Pulsed drain current	$I_{D, \text{pulse}}$		80	A
Maximum gate source voltage	$V_{GS(max)}$		-10/+22	V
Operational gate source voltage	$V_{GS \text{ op}}$		-6/+18	V
Power dissipation	P_{tot}		187.5	W
Storage temperature	T_{stg}		-55 to +175	$^\circ\text{C}$
Operating temperature	T_j			

^a Pulse width limited by T_{jmax}

Parameter	Symbol	Conditions	Values			Unit
			Min	Typ	Max	

Thermal characteristics

Thermal resistance, junction-case	R_{thJC}		-	-	0.8	°C/W
Thermal resistance, junction-ambient	R_{thJA}	leaded	-	-	40	
Soldering temperature, wave soldering only allowed at leads	T_{solder}	1.6mm (0.063in.) from case for 10 s	-	-	260	°C

Electrical characteristics^a, at $T_j=25^{\circ}\text{C}$, unless otherwise specified

Static characteristics

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=100\mu A$	1200	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=5mA$	2.2	3.2	4.5	
		$V_{DS}=V_{GS}, I_D=5mA, T_j=175^{\circ}\text{C}$	-	2.2	-	
Zero gate voltage drain current	I_{DSS}	$V_{DS}=1200V, V_{GS}=0V$	-	5	50	μA
Gate source leakage current	I_{GSS}	$V_{GS}=-6/+18V, V_{DS}=0V$	-	-	± 100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$V_{GS}=18V, I_D=20A$	-	80	95	m Ω
		$V_{GS}=18V, I_D=20A, T_j=175^{\circ}\text{C}$	-	128	-	
Gate resistance	R_G	$f=1\text{ MHz}, V_{AC}=25mV$	-	5.4	-	Ω

Dynamic characteristics

Input capacitance	C_{iss}	$V_{DS}=800V, V_{GS}=0V, f=100\text{ kHz}, V_{AC}=25mV$	-	1295	-	pF
Output capacitance	C_{oss}		-	65	-	
Reverse transfer capacitance	C_{rss}		-	8	-	
C_{OSS} stored energy	E_{oss}		-	26	-	μJ
Forward transconductance	g_{FS}	$V_{DS}=20V, I_D=20A$	-	11	-	S
Turn-on delay time	$t_{d(on)}$	$V_{DS}=800V, V_{GS}=-5/+18V, I_D=20A, R_G=5\Omega$ (External) $L=99\mu H$	-	14	-	ns
Rise time	t_r		-	10	-	
Turn-off delay time	$t_{d(off)}$		-	21	-	
Fall time	t_f		-	17	-	
Turn-on switching energy	E_{ON}	Diode: Body Diode at $V_{GS}=-5V$	-	625	-	μJ
Turn-off switching energy	E_{OFF}		-	57	-	

Parameter	Symbol	Conditions	Values			Unit
			Min	Typ	Max	

Dynamic characteristics

Turn-on delay time	$t_{d(on)}$	$V_{DS}=800V, V_{GS}=-5/+18V,$ $I_D=20A, R_G=5\Omega$ (External), $L=99\mu H, T_j=175^\circ C$	-	13	-	ns
Rise time	t_r		-	8	-	
Turn-off delay time	$t_{d(off)}$		-	23	-	
Fall time	t_f		-	15	-	
Turn-on switching energy	E_{ON}	Diode: Body Diode at $V_{GS}=-5V$ $T_j=175^\circ C$	-	579	-	μJ
Turn-off switching energy	E_{OFF}		-	54	-	

Gate Charge Characteristics

Gate to source charge	Q_{gs}	$V_{DS}=800V, I_D=20A,$ $V_{GS}=-5$ to $+18V$	-	17	-	nC
Gate to drain charge	Q_{gd}		-	36	-	
Gate charge total	Q_g		-	68.6	-	

Reverse Diode

Continuous forward current	I_S	$V_{GS}=-4V$	-	-	35.1	A
Diode forward voltage	V_{SD}	$V_{GS}=-4V, I_{SD}=20A$	-	5	-	V
		$V_{GS}=-4V, I_{SD}=20A,$ $T_j=175^\circ C$	-	3.4	-	
Reverse recovery time	t_{rr}	$V_{GS}=-4V, V_{RR}=800V,$ $I_{SD}=20A,$ $d_iF/d_t=460 A/\mu s$	-	17	-	ns
Reverse recovery charge	Q_{rr}		-	44	-	nC
Peak reverse recovery current	I_{rm}		-	5	-	A




Figure 1: Output Characteristics $T_J = -40^{\circ}\text{C}$




Figure 2: Output Characteristics $T_J = 25^{\circ}\text{C}$




Figure 3: Output Characteristics $T_J = 175^{\circ}\text{C}$




Figure 4: Normalized On-Resistance vs. Temperature




Figure 5: On-Resistance vs. Drain Current For Various Temperatures




Figure 6: On-Resistance vs. Temperature For Various Gate Voltage




Figure 7: Transfer Characteristics For Various Junction Temperature




Figure 8: Body Diode Characteristics at -40°C




Figure 9: Body Diode Characteristics at 25°C




Figure 10: Body Diode Characteristics at 175°C




Figure 11: Threshold Voltage vs. Temperature




Figure 12: Gate-Charge Characteristics




Figure 13: 3rd Quadrant Characteristics at -40°C




Figure 14: 3rd Quadrant Characteristics at 25°C




Figure 15: 3rd Quadrant Characteristics at 175°C




Figure 16: Output Capacitor Stored Energy




Figure 17: Capacitance Characteristics (0-200V)




Figure 18: Capacitance Characteristics (0-1200V)




Figure 19: Current De-rating




Figure 20: Maximum Power Dissipation Derating vs Case Temperature




Figure 21: Normalized Maximum Transient Thermal Impedance




Figure 22: Maximum Forward Biased Safe Operating Area




Figure 23: Clamped Inductive Switching Energy vs. $R_{G(ext)}$




Figure 24: Clamped Inductive Switching Energy vs. T_J




Figure 25: Clamped Inductive Switching Energy vs. Drain Current ($V_{DD} = 600\text{ V}$)





Figure 26: Clamped Inductive Switching Energy vs. Drain Current ($V_{DD} = 800\text{ V}$)


Package Outline: TO-247



NOTE:

1. ALL METAL SURFACES: TIN PLATED EXCEPT AREA OF CUT
2. DIMENSIONING & TOLERANCING CONFIRM TO ASME Y14.5M-1994.
3. ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES ARE IN DEGREES.
4. THIS DRAWING WILL MEET ALL DIMENSIONS REQUIREMENT OF JEDEC OUTLINES TO-247 AD.

- 1 - GATE
- 2 - DRAIN (COLLECTOR)
- 3 - SOURCE (EMITTER)
- 4 - DRAIN (COLLECTOR)



Package Outline: TO-247

SYMBOL	MIN	MAX
A	4.83	5.21
A1	2.29	2.54
A2	1.91	2.16
b'	1.07	1.28
b	1.07	1.33
b1	1.91	2.41
b2	1.91	2.16
b3	2.87	3.38
b4	2.87	3.13
c'	0.55	0.65
c	0.55	0.68
D	20.80	21.10
D1	16.25	17.65
D2	0.95	1.25
E	15.75	16.13
E1	13.10	14.15
E2	3.68	5.10
E3	1.00	1.90
E4	12.38	13.43
e	5.44 BSC	
N	3	
L	19.81	20.32
L1	4.10	4.40
ØP	3.51	3.65
Q	5.49	6.00
S	6.04	6.30
T	17.5° REF.	
W	3.5° REF.	
X	4° REF.	

Marking Information


YY = Last two digits of the year

WW = Work week

***** = Site ID

XXXXXX = Lot ID

ICE80M120 = ICE is IceMOS logo and 80M120 is a designated device part number



Disclaimer

Information contained in this data sheet shall in no event be regarded as a guarantee of conditions or characteristics. All product, data sheet are subject to change without notice to improve reliability. ICEMOS technology will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet.